Application Number: 10/087,522 Dkt. No.:14347

Reply to O.A. of May 13, 2005

LISTING OF THE CLAIMS

The listing of claims will replace all prior versions, and listings, of claims in the

application.

1-7. (canceled)

8-29. (canceled)

30. (Previously Presented) A device for measuring fluids in a body, comprising:

a structure having an inlet portion, an access portion, and an outlet portion, the

access portion being implantable in the body when the device measures the fluids in the body

and being in fluid communication between the inlet portion and the outlet portion, wherein the

access portion has a fluid channel in which a dialysis fluid flows from the inlet portion to the

outlet portion whereby constituents of the fluids in the body are picked up by the dialysis fluid

flowing through the access portion; and

a sensor being arranged in the fluid channel in vicinity of the outlet portion, the

sensor being disposed outside of the body when the access portion is implanted in the body to

measure the fluids in the body.

31. (Previously Presented) The device of claim 30, wherein the sensor is arranged such that the

sensor is removable.

32. (Previously Presented) The device of claim 30, further comprising a valve, the valve being

arranged in the fluid channel in the vicinity of the outlet portion for preventing a reverse flow of

the dialysis fluid from the sensor into the access portion.

33. (Previously Presented) The device of claim 30, wherein the fluid channel is formed by a

supply tube and a discharge tube, the supply tube is in fluid communication with the inlet portion

whereby the dialysis fluid flows from the inlet portion to the supply tube, the discharge tube is in

fluid communication with the outlet portion whereby the dialysis fluid flows from the discharge

-2-

Application Number: 10/087,522 Dkt. No.:14347

Reply to O.A. of May 13, 2005

tube to the outlet portion, and the supply tube and the discharge tube are connected to each other whereby the dialysis fluid flows from the supply tube to the discharge tube.

34. (Previously Presented) The device of claim 30, wherein the access portion is surrounded by

a membrane through which the constituents of the fluids in the body are picked up by the dialysis

fluid flowing through the access portion.

35. (Previously Presented) The device of claim 30, further comprising a supporting plate for

supporting the access portion, wherein when the device measures the fluids in the body, the

access portion is implanted in the body, and the supporting plate is disposed outside the body

between the body and the inlet portion.

36. (Previously Presented) The device of claim 30, further comprising a supporting plate for

supporting the access portion, wherein when the device measures the fluids in the body, the

access portion is implanted in the body, and the supporting plate is disposed outside the body

between the body and the outlet portion.

37. (Previously Presented) The device of claim 30, further comprising a supporting plate for

supporting the access portion, wherein when the device measures the fluids in the body, the

access portion is implanted in the body, and the supporting plate is disposed outside the body

between the body and the inlet and outlet portions.

-3-